



## BEAM UB302B

### Description

Beam UB302B is a fast drying black bituminous and wax based paint suitable for application on metal surfaces.

### Suggested uses

Corrosion preventative treatment for automotive chassis and underbodies, steel and alloys.

### Technical Data

Product code:	UB302B
Colour:	Black
Recommended Thinner:	Not Recommended – White Spirits 5% – 10%.
Drying Times:	At normal ambient conditions and nominal film thickness of 250 microns. <ul style="list-style-type: none"> <li>• Touch Dry - 60 minutes</li> <li>• Hard Dry - 24 hours</li> </ul>
Recoat:	Overnight
Shelf Life:	24 months
Surface Preparation:	New OEM Finishes and Metal surfaces should be dry and dirt free... Lightly Rusted Surfaces should be cleaned and pre-treated with "Beam RX401" rust converter. Heavily Rusted Surfaces ideally should be whip or sand blasted (or wire brushing at a minimum) then pre-treated with "Beam RX401" rust converter.,
Pack Sizes:	1 Litre, 5 Litre, 20 Litre, 200 Litre

### Precautions:

Beam UB302B contains highly flammable solvents and therefore should be stored away from heat and open flames. Do not smoke whilst using. When applying in a confined space use an air line respirator. Do not allow spilt product to remain on the skin. Normal health and hygiene standards should be observed when using this product.

### Application Remarks:

<b>Conventional Air Spray:</b>	Typical set up 300-400 kPa, 1.7-2.5 mm Fluid Nozzle.
<b>Airless Spray:</b>	Typical set up 30:1 pump ratio with a fluid tip of approximately 432 micrometers (0.017inch) and a nozzle pressure of 14 MPa (2000 psi).
<b>Brush/Roller:</b>	Apply a full even coat to the recommended film build.
<b>Clean up:</b>	Kerosene or White Spirits.

### Health and Safety:

Contains highly flammable volatile solvents. Keep away from all sources of heat and open flames. Do not smoke whilst handling. Wear suitable protective clothing to avoid contact with skin and eyes and avoid breathing vapour. Do not spray in confined or poorly ventilated areas without the use of approved air supplied breathing apparatus.

### Cleaning and Storage:

Close the container tightly to prevent air penetration. Store in roofed and ventilated place.

### Caution:

Keep away from fire, inedible, keep out of reach of children. Use in a well ventilated area only. Protect eyes and skin when working with paint. Use suitable equipment, clothing and protective gloves. Refrain from inhaling fumes. Wash hands with soap and water after painting. Do not apply when rain is expected or when temperatures drop below 10°C and relative humidity is over 85%.

### General Comments:

Achievement of the best desired results is subject to proper application in strict conformance to our instructions and safety measures. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared and are suitable for the products application. Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.

REVISED: March 2012

This information is furnished without warranty, representation, inducement or license of any kind except that it is accurate to the best of our knowledge. Beam does not assume any legal responsibility for use or reliance upon the same. Customers are encouraged to conduct their own tests. This information is non-controlled. It is the responsibility of the user to ensure that the issue is current.